

# ZR125KC-TFD



HCFC, R-22, Mid Point, 50 Hz, 3 - Phase, 380/420 V

Air Conditioning

**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45/130	45/100
RG(°F)/Liq(°F)	65/115	65/85
Capacity (Btu/hr):	106000	124000
Power (Watts):	9000	6300
Current (Amps):	15.8	12.3
EER (Btu/Wh):	11.8	19.7
Mass Flow (lbs/hr):	1550.0	1600.0
Sound Power(dBA):	75 Ave	80 Max
Vibration (mils(peak-peak)):	3.0 Ave	4.5 Max
Record Date:	2006-02-13	

## Mechanical

Number of Cylinders:	0	Displ (in <sup>3</sup> /Rev):	10.198
Bore Size (in):	0.0	Displ (ft <sup>3</sup> /hr):	1026.877
Stroke (in):	0.0		
Overall Length (in):	10.38	Mounting Length (in):	7.5
Overall Width (in):	11.23	Mounting Width(in):	7.5
Overall Height (in):	21.0	Mounting Height (in):	21.75*
Suction Size (in):	1 3/8 Stub		
Discharge Size (in):	7/8 Stub		
Initial Oil Charge (oz):	110		
Oil Recharge (oz):	106		
Net Weight (lbs):	135.0		
Internal Free Volume (in <sup>3</sup> ):	809.0		
HorsePower	10.0		
* Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	118.0	MCC (Amps):	26.9	UL File No.:	SA-2337
LRA-Half Winding:		RPM:	2900	UL File Date:	27-Sep-1996
LRA-Low*:	110.0	Max Operating Current:	19.6	CSA File No.:	LR3104C
RLA(=MCC/1.4; use for contactor selection):	19.2				
RLA (=MCC/1.56; use for breaker & wire size selection):	17.2				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Frequency(Hz)	Phase	Voltage	Application
R-22 HCFC	60	3	460	Air Conditioning