

2. Specification

Model No.		MKA-600R(A)	MKA-750R(A)	MKA-850R(A)	
Airflow (Hi-speed)	CFM	600	750	850	
	m ³ /h	1000	1250	1400	
Cooling Capacity (Hi-speed)	W	5718	6987	7268	
	Btu/h	19510	23840	24800	
Heating Capacity (Hi-speed)	W	9663	11553	12415	
	Btu/h	32970	39420	42360	
Noise (Hi-speed)	dB(A)	45	46	47	
Water Flow	l/min	16.4	20.0	20.8	
Water Pressure Drop	kPa	23.8	25.2	27	
Indoor Coil	Number Of Rows	2	2	2	
	Tube Pitch(A)×Row Pitch(B)	mm	21×13.37		
	Fin Spacing	mm	1.5		
	Fin Type		Hydrophilic aluminum		
	Tube Outside Dia. And Type	mm	φ7, bare tube		
	Coil dimension (LxHxW)	mm	1959.4×168×26.74	1959.4×252×26.74	
	Number Of Circuits		8	12	
Fan Motor	Type		Low noise 4-speed fan motor		
	Number		1		
	Model		YDK80-6E	YDK90-6E	
	Input	W	120/110/100/90	120/110/100/90	165/143/116/100
	Capacitor	uF	3uF/450V	3.5uF/450V	2.5uF/450V
Auxiliary Electrical Heater	kW	2.1	2.1	2.7	
Indoor Unit	Dimension (W×H×D)	mm	840×230×840		
	Packing (W×H×D)	mm	955×247×955		
	Net/Gross Weight	kg	29/36		
Panel	Dimension (W×H×D)	mm	950×46×950		
	Packing (W×H×D)	mm	1035×90×1035		
	Net/Gross Weight	kg	6/9		
Control Mode		wired controller(optional), remote controller (standard)			
Pipe	Water-Inlet Pipe		RC3/4" internal thread		
	Water-Return Pipe		RC3/4" internal thread		
	Condensation Water-Outlet Pipe		EVA+LDPE 3/4" external thread		

- Remark:**
- All performance data above is based upon 0Pa ambient static pressure.
 - Cooling capacity test condition: air inlet Temp. : 27DB°C/19WB°C, water inlet Temp. 7°C, water Temp. difference 5°C.
 - Heating capacity test condition:
Air inlet Temp. 21DB°C, water inlet Temp. 60 DB°C
The volume of air and water is same as cooling.
 - Noise level is tested in full-anechoic room.
 - The auxiliary electrical heater is only available for MKA-XXXRA series.

در صورت داشتن هرگونه سوال در مورد اطلاعات فنی و قیمت با شماره های شرکت همگام تجارت هواسنج تم اس حاصل فرمایید :

02177262514-090102016100

Havasanj.ir

Model No.		MKA-950R(A)	MKA-1200R(A)	MKA-1500R(A)
Airflow (Hi-speed)	CFM	950	1200	1500
	m ³ /h	1600	2000	2550
Cooling Capacity (Hi-speed)	W	8220	10390	12866
	Btu/h	28050	35450	43900
Heating Capacity (Hi-speed)	W	13845	17585	21043
	Btu/h	47240	60000	71800
Noise (Hi-speed)	dB(A)	48	49	49
Water Flow	l/min	23.6	29.8	36.9
Water Pressure Drop	kPa	31.2	44	46
Indoor Coil	Number Of Rows	2		
	Tube Pitch(A)×Row Pitch(B)	mm	21×13.37	
	Fin Spacing	mm	1.5	
	Fin Type	Hydrophilic aluminum		
	Tube Outside Dia. And Type	mm	φ7, bare tube	
	Coil dimension (L×H×W)	mm	1959.4×252×26.74	
	Number Of Circuits	12		
Fan Motor	Type	Low noise 4-speed fan motor		
	Number	1		
	Model	YDK90-6E		
	Input	W	165/143/116/100	
	Capacitor	uF	3uF/450V	3.5uF/450V
Auxiliary Electrical Heater	kW	2.7		
Indoor Unit	Dimension (W×H×D)	mm	840×300×840	
	Packing (W×H×D)	mm	955×317×955	
	Net/Gross Weight	kg	35/42	
Panel	Dimension (W×H×D)	mm	950×46×950	
	Packing (W×H×D)	mm	1035×90×1035	
	Net/Gross Weight	kg	6/9	
Control Mode	wired controller(optional), remote controller (standard)			
Pipe	Water-Inlet Pipe	RC3/4" internal thread		
	Water-Return Pipe	RC3/4" internal thread		
	Condensation Water-Outlet Pipe	EVA+LDPE 3/4" external thread		

Remark:

- All performance data above is based upon 0Pa ambient static pressure.
- Cooling capacity test condition: air inlet Temp. : 27DB°C/19WB°C, water inlet Temp. 7°C, water Temp. difference 5°C.
- Heating capacity test condition: Air inlet Temp. 20DB°C, water inlet Temp. 50 DB°C, the volume of air and water is same as cooling.
- Noise level is tested in full-anechoic room.
- The auxiliary electrical heater is only available for MKA-XXXRA series.

در صورت داشتن هرگونه سوال در مورد اطلاعات فنی و قیمت با شماره های شرکت همگام تجارت هواسنج تم اس حاصل فرمایید :

02177262514-090102016100

Havasanj.ir