

ELITE

		108	113	117	121	124	228
❶ Cooling Capacity	kw	7.81	13.4	17.1	21	23.7	27.6
❶ Absorbed Power	kw	3.03	4.86	6.58	7.69	8.31	10.66
❶ E.E.R		2.58	2.76	2.60	2.73	2.85	2.59
❶ ESEER		3.98	4.22	3.98	4.19	4.37	3.96
❷ Sound power Level	db(A)	46	46	47	47	47	47
Scroll Compensor No	no	1	1	1	1	1	2
Step Compensor	no	1	1	1	1	1	2
Circuits	no	1	1	1	1	1	1
Electrical Suplly	V-Ph-Hz	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50	380/3/50
		1.2	2.1	2.7	3.3	3.7	4.3
W- width	mm	456	456	456	456	456	456
D- depth	mm	1230	1230	1230	1697	1697	1697
H- Height	mm	1473	1453	1567	1567	1567	1567
❸ Weight	Kg	136	144	155	247	250	290
Refrigerant		R-407A - R-410A					

Performance according to EN 14511.

- ❶ Outdoor air temperature 35°C DB/24°C WB - chilled water temperature inlet/outlet 12/7°C.
 - ❷ In open Field (Q = 2) at 10 m from the unit
 - ❸ Total sound power level in dB(A) based on measurements carried out in accordance with regulation UNI EN-ISO 9614.
 - ❹ Weight referred to the unit without load and not accessorised
- silent version

