

# TOSHIBA Leading Innovation >>>

DIGITAL INVERTER



## RAV Ducted Systems Digital Inverter

System Retail Price*	£1,277	£1,472	£2,137	£2,587	£2,839	£3,347
Indoor Unit (ID) + Wired Controller	RAV-SM406BTP-E	RAV-SM566BTP-E	RAV-SM806BTP-E	RAV-SM1106BTP-E	RAV-SM1406BTP-E	RAV-SM1606BTP-E
Outdoor Unit (OD)	RAV-SM404ATP-E	RAV-SM564ATP-E	RAV-SM804ATP-E	RAV-SM1104ATP-E	RAV-SM1404ATP-E	RAV-SM1603AT-E
Nominal Cooling Capacity, kW	3.6	5.0	6.7	10.0	12.1	14.0
Nominal Heating Capacity, kW	4.0	5.3	7.7	11.2	12.8	16.0
SEER/SCOP - Energy Rating	5.06/3.95 - B/A	4.80/3.98 - B/A	5.04/3.83 - B/A	5.03/4.14 - B/A+	5.53/4.42 - A/A+	4.78/3.86 - B/A
Sound Pressure ID - OD**, dB(A)	33/29/25 - 45/47	33/29/25 - 46/48	34/30/26 - 48/52	40/36/33 - 53/54	40/36/33 - 54/55	40/36/33 - 51/53
Dimensions - ID (H x W x D), mm	275 x 700 x 750	275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750
Dimensions - OD (H x W x D), mm	550 x 780 x 290	550 x 780 x 290	550 x 780 x 290	890 x 900 x 320	890 x 900 x 320	1340 x 900 x 320
Weight ID - OD, kg	23 - 39	23 - 40	30 - 44	40 - 68	40 - 68	40 - 99
Power Supply OD - ID cable	10 A/1 ph - 3 core + earth	16 A/1 ph - 3 core + earth	16 A/1 ph - 3 core + earth	20 A/1 ph - 3 core + earth	32 A/1 ph - 3 core + earth	32 A/1 ph - 3 core + earth
R410A Pipe Sizes, Gas - Liquid, mm (inch)	12.7 (1/2) - 6.4 (1/4)	12.7 (1/2) - 6.4 (1/4)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)
R410A Pipe Min./Max. Length - Height, m	2/20 - 10	5/30 - 30	5/30 - 30	5/50 - 30	5/50 - 30	5/50 - 30
R410A Charge Length, m (kg) - Addition, g/m	15 (1.4) - 20	20 (1.1) - 20	20 (1.7) - 40	30 (2.8) - 40	30 (2.8) - 40	30 (3.1) - 40

در صورت داشتن هرگونه سوال در مورد اطلاعات فنی و قیمتی محصولات، با شماره های شرکت همگام تجارت هواسنج تماس حاصل فرمایید:

۰۲۱-۷۷۲۶۲۵۱۴ ۰۹۱۰۲۰۱۶۱۰۰

[www.havasanj.ir](http://www.havasanj.ir)

# TOSHIBA Leading Innovation >>>

SUPER DIGITAL INVERTER



## RAV Ducted Systems Super Digital Inverter

System Retail Price*	£1,527	£1,652	£2,432	£2,947	£3,322	£3,254	£3,504	£3,937
Indoor Unit (ID) + Wired Controller	RAV-SM406BTP-E	RAV-SM566BTP-E	RAV-SM806BTP-E	RAV-SM1106BTP-E	RAV-SM1106BTP-E	RAV-SM1406BTP-E	RAV-SM1406BTP-E	RAV-SM1606BTP-E
Outdoor Unit (OD)	RAV-SP404ATP-E	RAV-SP564ATP-E	RAV-SP804ATP-E	RAV-SP1104AT-E	RAV-SP1104AT8-E	RAV-SP1404AT-E	RAV-SP1404AT8-E	RAV-SP1604AT8-E
Nominal Cooling Capacity, kW	3.6	5.0	7.1	10.0	10.0	12.5	12.5	14.0
Nominal Heating Capacity, kW	4.0	5.6	8.0	11.2	11.2	14.0	14.0	16.0
SEER/SCOP - Energy Rating	5.10/4.02 - A/A+	4.88/4.01 - B/A+	5.88/4.00 - A+/A	5.65/3.87 - A+/A	5.65/3.87 - A+/A	5.22/4.03 - A/A+	5.09/4.48 - B/A+	4.97/4.35 - B/A+
Sound Pressure ID - OD**, dB(A)	33/29/25 - 45/47	33/29/25 - 47/48	34/30/26 - 48/49	40/36/33 - 49/50	40/36/33 - 49/50	40/36/33 - 51/52	40/36/33 - 51/52	40/36/33 - 51/53
Dimensions - ID (H x W x D), mm	275 x 700 x 750	275 x 700 x 750	275 x 1000 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750	275 x 1400 x 750
Dimensions - OD (H x W x D), mm	550 x 780 x 290	550 x 780 x 290	890 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320	1340 x 900 x 320
Weight ID - OD, kg	23 - 40	23 - 44	30 - 66	40 - 93	40 - 95	40 - 93	40 - 95	40 - 95
Power Supply OD - ID cable	10 A/1 ph - 3 core + earth	16 A/1 ph - 3 core + earth	16 A/1 ph - 3 core + earth	16 A/1 ph - 3 core + earth	10 A/3 ph - 3 core + earth	25 A/1 ph - 3 core + earth	16 A/3 ph - 3 core + earth	16 A/3 ph - 3 core + earth
R410A Pipe Sizes, Gas - Liquid, mm (inch)	12.7 (1/2) - 6.4 (1/4)	12.7 (1/2) - 6.4 (1/4)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)	15.9 (5/8) - 9.5 (3/8)
R410A Pipe Min./Max. Length - Height, m	5/30 - 30	5/50 - 30	5/50 - 30	3/75 - 30	3/75 - 30	3/75 - 30	3/75 - 30	3/75 - 30
R410A Charge Length, m (kg) - Addition, g/m	20 (1.0) - 20	20 (1.4) - 20	30 (2.1) - 40	30 (3.1) - 40	30 (3.1) - 40	30 (3.1) - 40	30 (3.1) - 40	30 (3.1) - 40

\* System price includes RBC-AMT32E (E52) standard remote controller, but excludes spigots

\*\* Figures given for the Indoor Unit are at high/medium/low fan speeds, and for the Outdoor Unit for cooling/heating